


NATO UNCLASSIFIED



NATO Communications and Information Agency
Agence OTAN d'information et de communication

AGENCY INSTRUCTION
INSTR TECH 06.02.05
SERVICE INTERFACE PROFILE FOR ENTERPRISE DIRECTORY SERVICES

Effective date:

Revision No: Original

Issued by: Chief, Core Enterprise Services *[Signature]*

Approved by: Director Service Strategy *[Signature]*

NATO UNCLASSIFIED

Table of Amendments

Amendment No	Date issued	Remarks

Author Details

Organization	Name	Contact Email/Phone
NCI Agency	L. Schenkels	leon.schenkels@ncia.nato.int
NCI Agency	G. Lunt	

Table of Contents

	PAGE
0 PRELIMINARY INFORMATION	4
0.1 References-----	4
0.2 Purpose-----	4
0.3 Applicability -----	4
1 SIP INTRODUCTION	4
1.1 Audience -----	5
1.2 Notational conventions -----	5
1.3 Terminology-----	5
1.4 Goals -----	5
1.5 Non-Goals-----	6
1.6 Relationships to Other Profiles and Specifications -----	6
2 SIP DEFINITION	6
2.1 Subject-----	6
2.2 Service interface -----	7
2.3 Operations-----	7
2.4 Message Structure-----	9
3 SCHEMA	11
3.1 Introduction-----	11
3.2 Base Schema -----	11
3.3 Extended Schema-----	11
3.4 Naming -----	11
4 REFERENCES	13
5 ABBREVIATIONS	16

List of Annexes

ANNEX 1 – LDAP REPRESENTATION OF THE BASE DIRECTORY SCHEMA	17
---	-----------

AGENCY INSTRUCTION 06.02.05

SERVICE INTERFACE PROFILE FOR ENTERPRISE DIRECTORY SERVICES

0 PRELIMINARY INFORMATION

0.1 References

- A. NCIA/GM/2012/235; Directive 1 Revision 1; dated 3 May 2013
- B. NCIARECCEN-4-22852 DIRECTIVE 01.01, Agency Policy on Management and Control of Directives, Notices, Processes, Procedures and Instructions, dated 20 May 2014
- C. NCIARECCEN-4-23297, Directive 06.00.01, Management and Control of Directives, Processes, Procedures and Instructions on Service Management, dated 03 June 2014

0.2 Purpose

This Technical Instruction (TI) provides detailed information, guidance, instructions, standards and criteria to be used when planning, programming, and designing Agency products and services. In this specific case the TI defines a Service Interface Profile (SIP) for one of NATO's Core Enterprise Services.

TIs are living documents and will be periodically reviewed, updated, and made available to Agency staff as part of the Service Strategy responsibility as Design Authority. Technical content of these instructions is the shared responsibility of SStrat/Service Engineering and Architecture Branch and the Service Line of the discipline involved.

TIs are primarily disseminated electronically¹, and will be announced through Agency Routine Orders. Hard copies or local electronic copies should be checked against the current electronic version prior to use to assure that the latest instructions are used.

0.3 Applicability

This TI applies to all elements of the Agency, in particular to all NCI Agency staff involved in development of IT services or software products. It is the responsibility of all NCI Agency Programme, Service, Product and Project Managers to ensure the implementation of this technical instruction and to incorporate its content into relevant contractual documentation for external suppliers.

1 SIP INTRODUCTION

In order to ensure compatibility between services, both within NATO and between NATO and its partners, there is a need to ensure that a standard (and standards-based) profile can be defined which will be mandatory for all service operations in the NATO Network Enabled Capability (NNEC).

A range of separate directories and data repositories coexist within NATO with a sizeable overlap between the information contained within these various directories. There is a need for synchronization between them to harmonise and rationalise the information which can be facilitated by an Enterprise Directory Service.

The Enterprise Directory Service can serve as a central information repository in an enterprise network infrastructure, storing identity, authorization, and application-specific information, service-publication and discovery information, as well as directory service configuration data. A directory service is an inherent part of distributed security and identity management, and plays a key role in the manageability of a distributed enterprise.

¹ [https://servicestrategy.nr.ncia/SitePages/Agency%20Directives%20\(Technical\).aspx](https://servicestrategy.nr.ncia/SitePages/Agency%20Directives%20(Technical).aspx)

The purpose of this Service Interface Profile (SIP) is to specify the interface of the directory service itself. Though the Enterprise Directory Services is often referred to as a capability also including adapters to a variety of data sources like for instance file interfaces such as LDAP data interchange format (LDIF) and comma-separated value (CSV), or database interfaces using structured query language (SQL), this specification will entirely focus on the directory service interface. The additional interfaces are to be provided through separate agents that are able to translate various sources to the protocol used by the directory service as specified in this document.

1.1 Audience

The target audience for this specification is the broad community of NNEC stakeholders, who are delivering capability in an NNEC environment, or anticipate that their services may be used in this environment.

These may include (but are not limited to):

- Project Managers procuring Bi-SC (Bi-Strategic Commands) or NNEC related systems
- The architects and developers of service consumers and providers
- Coalition partners whose services may need to interact with NNEC services
- Systems integrators delivering systems into the NATO environment.

1.2 Notational conventions

The following notational conventions apply to this document:

- The keywords "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [IETF RFC 2119, 1997].
- Words in *italics* indicate terms referenced in Section 1.3.

1.3 Terminology

Table 1
Terminology

<i>Directory interrogation</i>	The search and retrieval of information from the directory.
<i>Directory modification</i>	Adding, deleting and modifying entries within the directory.
<i>Directory schema</i>	Definition of the attributes and their optional or mandatory presence in a directory entry of a given object class.
<i>Distinguished Name</i>	A name that uniquely identifies an entry within the directory, consisting of a sequence of relative distinguished names.
<i>RootDSE</i>	An entry within the directory server that contains information about the directory server itself, including its capabilities and configuration.

1.4 Goals

The following are the goals of this profile:

- Identifying the protocol used to access the Enterprise Directory Service

- Identifying the authentication mechanisms to be used
- Identifying the security mechanisms to be used.

1.5 Non-Goals

The following topics are outside the scope of this profile:

- Identifying the complete Enterprise Directory Service schema.

1.6 Relationships to Other Profiles and Specifications

Relationships with other CES Service Interface Profiles are among others:

- Security Token Service (see [NCIA TR/2012/CPW007253/02, 2012]) – Enterprise Directory Services can act as an Identity Provider.
- Collaboration Services (see [NC3A RD-3186, 2011] – Enterprise Directory Services can provide common user data to collaboration services.

1.6.1 Normative References

The following documents have fed into this specification, and are incorporated as normative references:

1.6.1.1 General

- Lightweight Directory Access Protocol (LDAP): Technical Specification Road Map, [IETF RFC 4510, 2006]
- Lightweight Directory Access Protocol (LDAP): The Protocol, [IETF RFC 4511, 2006]
- Lightweight Directory Access Protocol (LDAP): Directory Information Models, [IETF RFC 4512, 2006]
- Lightweight Directory Access Protocol (LDAP): Authentication Methods and Security Mechanisms, [IETF RFC 4513, 2006]
- Lightweight Directory Access Protocol (LDAP): String Representation of Distinguished Names, [IETF RFC4514, 2006]
- Lightweight Directory Access Protocol (LDAP): String Representation of Search Filters, [IETF RFC 4515, 2006]
- Lightweight Directory Access Protocol (LDAP): Uniform Resource Locator, [IETF RFC 4516, 2006]
- Lightweight Directory Access Protocol (LDAP): Syntaxes and Matching Rules, [IETF RFC 4517, 2006]
- Lightweight Directory Access Protocol (LDAP): Internationalized String Preparation, [IETF RFC 4518, 2006].

1.6.1.2 Schema Documentation

- Definition of the LDAP iNetOrgPerson Object Class, [IETF RFC 2798, 2000]
- Lightweight Directory Access Protocol (LDAP): Schema for User Applications, [IETF RFC 4519, 2006]
- Allied Communication Publication 133(C), [CCEB ACP133C, 2007].

2 SIP DEFINITION

2.1 Subject

This SIP focuses on the interface profile of an Enterprise Directory Service. It is part of the *Repository* services as defined in the Core Enterprise Services Framework [NAC EAPC(AC/322-SC/1)N(2009)0015 (INV), 2009].

This SIP identifies and describes the mandatory service interfaces needed for the basic interoperability.

2.1.1 Directory Service Standards and XML

The Enterprise Directory Service is one of the services in the CES Framework that has existed for considerable time. Initial standards definitions were drafted by the International Telecommunication Union (ITU) as the X.500 series, but were soon overtaken by the more successful IETF LDAP standards, with an initial Request for Comments (RFC) for Version 2 in 1993 [IETF RFC 1487, 1993], followed-up by Version 3 in 1997 [IETF RFC 2251, 1997] which was further re-organized in 2006 [IETF RFC 4511, 2006]. Not only has the standard undergone substantial development and updates, it has also been well accepted and broadly implemented by vendors such as Microsoft and Oracle.

Whereas most of the CES Framework standards use extensible markup language (XML) encoding, LDAP uses abstract syntax notation (ASN) 1. Several attempts have been made to standardize a Directory Services specification based on XML, such as Directory Service Markup Language [OASIS DSML, 2002], Service Provisioning Markup Language [OASIS SPML, 2006] and XML-Enabled Directory [IETF DraftXED, 2007], but they have not been widely adopted.

2.2 Service interface

The service interface is not a web service and therefore a web services description language (WSDL) is not appropriate to describe the operations of the service.

The service interface is defined by IETF LDAP standards as defined in the LDAP Technical Specification Road Map [IETF RFC 4510, 2006].

2.3 Operations

The LDAP operations consist of a series of requests and responses, predominantly from the client to the server. The operations are grouped into three basic groups:

- 1) Association management – Bind/Unbind
- 2) Directory interrogation – Search/Compare/Abandon
- 3) Directory modification – Modify/Add/Delete/ModifyDN.

It is expected that the majority of the users of this SIP will perform *Directory Interrogation* and that a minority will perform directory modification operations. (All will perform association management operations.)

Table 2 shows the complete list of operations as described in [IETF RFC 4511, 2006].

Table 2
LDAP operations

Operation	Description
Bind	<i>Section 4.2:</i> The function of the Bind operation is to allow authentication information to be exchanged between the client and server. The Bind operation should be thought of as the “authenticate” operation.
Unbind	<i>Section 4.3:</i> The function of the Unbind operation is to terminate an LDAP session. The Unbind operation is not the antithesis of the Bind operation as the name implies. The naming of these operations are historical. The Unbind operation should be thought of as the “quit” operation.
Search	<i>Section 4.5:</i> The Search operation is used to request a server to return, subject to access controls and other restrictions, a set of entries matching a complex search criterion. This can be used to read attributes from a single entry, from entries immediately subordinate to a particular entry, or from a whole sub-tree of entries.
Modify	<i>Section 4.6:</i> The Modify operation allows a client to request that a modification of an entry be performed on its behalf by a server.
Add	<i>Section 4.7:</i> The Add operation allows a client to request the addition of an entry into the Directory.
Delete	<i>Section 4.8:</i> The Delete operation allows a client to request the removal of an entry from the Directory.
Modify DN	<i>Section 4.9:</i> The Modify DN operation allows a client to change the relative distinguished name (RDN) of an entry in the Directory and/or to move a sub-tree of entries to a new location in the Directory. The directory service must implement the interface as defined in Section 4.9 of [IETF RFC 4511, 2006].
Compare	<i>Section 4.10:</i> The Compare operation allows a client to compare an assertion value with the values of a particular attribute in a particular entry in the Directory.
Abandon	<i>Section 4.11:</i> The function of the Abandon operation is to allow a client to request that the server abandon an uncompleted operation.
Extended	<i>Section 4.12:</i> The Extended operation allows additional operations to be defined for services not already available in the protocol; for example, to Add operations to install transport layer security.

2.3.1 Authentication

The Bind operation allows a client to authenticate to the Enterprise Directory Service prior to interrogating or modifying the directory information.

The Enterprise Directory Service may allow parts of the directory information to be interrogated by all users, in which case no authentication is required during the Bind. This is termed “anonymous” access.

The Enterprise Directory Service may allow other parts of the directory information to only be interrogated by specific users, and will only allow the modification of directory information by other specific users. In both these cases authentication is required during the Bind.

The Enterprise Directory Service SHALL allow only three authentication modes:

- 1) Anonymous authentication – the user provides no credentials.
- 2) Simple authentication – the user provides a name and password that is specific to the Enterprise Directory Service.
- 3) Kerberos authentication – the user re-uses their domain credentials, which provides a single sign-on (SSO) capability. The more sophisticated Kerberos authentication uses simple authentication and security layer (SASL) [IETF RFC 4422, 2006] within the LDAP Bind operation.

If simple authentication is used then transport layer security (TLS) [IETF RFC 4346, 2006] SHALL be used to protect the credentials over the network. The TLS negotiation will also authenticate the Enterprise Directory Service to the client.

2.3.2 LDAP operation security

The users of the Enterprise Directory SIP will generally retrieve and publish authoritative information to the Enterprise Directory. As a result, the information being retrieved or published must be appropriately protected to ensure that the information is not tampered with in transit. Therefore all LDAP operations SHALL be protected by either:

- TLS, which encrypts the requests and results and provides indirect integrity.
- SASL integrity security layer (which signs the requests and results) negotiated during the authentication exchange.

Both TLS and SASL security layers SHALL NOT be used concurrently.

2.4 Message Structure

The following message structures are defined by [IETF RFC 4511, 2006].

2.4.1 Requests and responses

Paragraph 4.1.1 of [IETF RFC 4511, 2006] states that *“For the purposes of protocol exchanges, all protocol operations are encapsulated in a common envelope, the LDAPMessage, which is defined as follows”*:

```
LDAPMessage ::= SEQUENCE {
    messageID      MessageID,
    protocolOp     CHOICE {
        bindRequest      BindRequest,
        bindResponse     BindResponse,
        unbindRequest     UnbindRequest,
        searchRequest     SearchRequest,
        searchResEntry    SearchResultEntry,
        searchResDone     SearchResultDone,
        searchResRef      SearchResultReference,
        modifyRequest     ModifyRequest,
        modifyResponse    ModifyResponse,
```

```

addRequest      AddRequest,
addResponse     AddResponse,
delRequest      DelRequest,
delResponse     DelResponse,
modDNRequest    ModifyDNRequest,
modDNResponse   ModifyDNResponse,
compareRequest  CompareRequest,
compareResponse CompareResponse,
abandonRequest  AbandonRequest,
extendedReq     ExtendedRequest,
extendedResp    ExtendedResponse,
...,
intermediateResponse IntermediateResponse },
controls        [0] Controls OPTIONAL }

MessageID ::= INTEGER (0 .. maxInt)

maxInt INTEGER ::= 2147483647 -- (231 - 1) -

```

2.4.2 Errors

Paragraph 4.1.1 of [IETF RFC 4511, 2006] states that “*The LDAPResult is the construct used in this protocol to return success or failure indications from servers to clients. To various requests, servers will return responses containing the elements found in LDAPResult to indicate the final status of the protocol operation request.*”

```

LDAPResult ::= SEQUENCE {
    resultCode      ENUMERATED {
        success                      (0),
        operationsError              (1),
        protocolError                (2),
        timeLimitExceeded            (3),
        sizeLimitExceeded            (4),
        compareFalse                 (5),
        compareTrue                  (6),
        authMethodNotSupported       (7),
        strongerAuthRequired         (8),
        -- 9 reserved --
        referral                     (10),
        adminLimitExceeded           (11),
        unavailableCriticalExtension (12),
        confidentialityRequired      (13),
        saslBindInProgress           (14),
        noSuchAttribute              (16),
        undefinedAttributeType       (17),
        inappropriateMatching        (18),
        constraintViolation          (19),
        attributeOrValueExists       (20),
        invalidAttributeSyntax       (21),
        -- 22-31 unused --
        noSuchObject                 (32),
        aliasProblem                 (33),
        invalidDNSyntax              (34),
        -- 35 reserved for undefined isLeaf --
        aliasDereferencingProblem    (36),
        -- 37-47 unused --
        inappropriateAuthentication (48),
        invalidCredentials            (49),
        insufficientAccessRights     (50),
        busy                         (51),
        unavailable                  (52),
        unwillingToPerform           (53),
        loopDetect                   (54),
        -- 55-63 unused --
        namingViolation              (64),
        objectClassViolation         (65),
        notAllowedOnNonLeaf          (66),
    }
}

```

```

notAllowedOnRDN          (67),
entryAlreadyExists       (68),
objectClassModsProhibited (69),
-- 70 reserved for CLDAP --
affectsMultipleDSAs      (71),
-- 72-79 unused --
other                    (80),
... },
matchedDN                LDAPDN,
diagnosticMessage        LDAPString,
referral                  [3] Referral OPTIONAL }

```

These result codes are further detailed in Appendix A of [IETF RFC 4511, 2006], and also includes non-error conditions.

3 SCHEMA

3.1 Introduction

The Enterprise Directory Service maintains a well-defined directory schema and ensures that all the directory information it contains to the *Directory Schema*.

Core Enterprise Services that use the Enterprise Directory Service SIP for directory interrogation need a basic understanding of the *Directory Schema* to determine how to construct search filters to find specific entries within the directory and request the appropriate attributes.

Core Enterprise Services that use the Enterprise Directory Service SIP for *Directory Modification* need a complete understanding of the *Directory Schema* to ensure that the modifications they perform conform to the *Directory Schema*.

Note that though the *Directory Schema* will define all of the possible attributes and object classes that the Enterprise Directory Service may contain, the Enterprise Directory Service may not contain instances of all the object classes and attributes that are defined.

3.2 Base Schema

The Enterprise Directory Service contains a base *Directory Schema* that supports interoperability with NATO nations through the Alliance Replication Hub (ARH). This *Directory Schema* is defined in the ACP133 Edition C², ([CCEB ACP133C, 2007]).

An LDAP representation of the base directory schema is shown in Annex 1 .

3.3 Extended Schema

The *Directory Schema* is dynamic and will be extended as NATO authoritative sources publish their information to the Enterprise Directory Service. The current *Directory Schema* supported by the Enterprise Directory Service can be determined by sub-schema entries identified in the *RootDSE* of the Enterprise Directory Service.

3.4 Naming

The Enterprise Directory Service maintains two unique identifiers for all of the entries that it contains:

- *Distinguished Name* – a structured name that indicates the hierarchical name of the entry within the Enterprise Directory Service. This identifier would be used as the baseObject for a

² Note that ACP133 Edition D has been published but this has not yet been ratified by NATO.

baseObject search to read specific attributes from the entry. For example, "cn=Joe Smith, ou=Staff, ou=NC3A, o=NATO", which may have been obtained from the SubjectDN of an X.509 certificate.

- NATO Enterprise Identifier (NEID) – an attribute that contains a unique universal identifier (UUID) that is assigned to the entry when it is created. This identifier would be used within a search filter within a singleLevel or wholeSubtree search.

In addition, entries that conform to the ACP133 Edition C [CCEB ACP133C, 2007] *Directory Schema* may include the following unique identifiers:

- aCPEID – an attribute that specifies a globally unique identifier thus allowing each entry within a multinational directory to be identified.
- aCPEnterType/aCPEnterUniqueld – a pair of attributes that identify the entry type and an unique number within that entry type.

As the Enterprise Directory Service *Directory Schema* is extended, further unique naming attributes may be defined.

The aCPEID and aCPEnterType/aCPEnterUniqueld attributes, and other attributes (e.g. mail), may be used to identify entries within specific sub-trees within the Enterprise. However, the Enterprise Directory Service will not necessarily ensure their uniqueness. CESs that use these attributes should therefore be prepared to handle multiple matches.

4 REFERENCES

[NCIA AD 06.05.04.02.H]:

NATO Communications and Information Agency, Agency Directive 06.05.04.02.H, "Service Interface Profile for Security Services", R. Fiske, M. Lehmann, R. Malewicz, L. Schenkels, D. Gujral, NCIA, The Hague, Netherlands, to be published, (NATO Unclassified)

[CCEB ACP133C, 2007]:

Combined Communications-Electronics Board, "Common Directory Services and Procedures" CEB, October 2007.

[IETF DraftXED, 2007]:

Internet Engineering Task Force (on-line) <http://tools.ietf.org>, The XML-Enabled Directory: Protocols, S. Legg, at <http://tools.ietf.org/html/draft-legg-xed-protocols-05>, August 2007, viewed 19 May 2011.

[IETF RFC 1487, 1993]:

Internet Engineering Task Force (on-line) <http://tools.ietf.org>, Request for Comment 1487, "X.500 Lightweight Directory Access Protocol", W. Yeong, T. Howes, S. Kille, at <http://tools.ietf.org/html/rfc1487>, July 1993, viewed 19 May 2011.

[IETF RFC 2119, 1997]:

Internet Engineering Task Force (on-line) <http://tools.ietf.org>, Request for Comment 2119, "Keywords for use in RFCs to Indicate Requirement Levels", S. Bradner, at <http://tools.ietf.org/html/rfc2119>, March 1997, viewed 19 May 2011.

[IETF RFC 2251, 1997]:

Internet Engineering Task Force (on-line) <http://tools.ietf.org>, Request for Comment 2251, "Lightweight Directory Access Protocol (v3)", M. Wahl, T. Howes, S. Kille, December 1997, RFC2251, on-line at <http://tools.ietf.org/html/rfc2251> viewed 19 May 2011.

[IETF RFC 2798, 2000]:

Internet Engineering Task Force (on-line) <http://tools.ietf.org>, Request for Comment 2798, "Definition of the LDAP iNetOrgPerson Object Class", M. Smith, at <http://tools.ietf.org/html/rfc2798>, April 2000, viewed 19 May 2011.

[IETF RFC 4346, 2006]:

Internet Engineering Task Force (on-line) <http://tools.ietf.org>, Request for Comment 4346, "The Transport Layer Security (TLS) Protocol Version 1.1", T. Dierks, E. Rescoria. April 2006, at <http://tools.ietf.org/html/rfc4346>, viewed 19 May 2011.

[IETF RFC 4422, 2006]:

Internet Engineering Task Force (on-line) <http://tools.ietf.org>, Request for Comment 4422, "Simple Authentication and Security Layer (SASL)", A. Melnikov, Ed., K. Zeilenga, Ed., at <http://tools.ietf.org/html/rfc4422>, viewed 19 May 2011.

[IETF RFC 4510, 2006]:

Internet Engineering Task Force (on-line) <http://tools.ietf.org>, Request for Comment Lightweight Directory Access Protocol (LDAP): Technical Specification Road Map, K. Zeilenga, Ed., June 2006, RFC4510, on-line at <http://tools.ietf.org/html/rfc4510> viewed 19 May 2011.

[IETF RFC4511, 2006]:

Internet Engineering Task Force (on-line) <http://tools.ietf.org>, Request for Comment 4511, "Lightweight Directory Access Protocol (LDAP): The Protocol", J. Sermersheim, at <http://tools.ietf.org/html/rfc4511>, June 2006, viewed 19 May 2011.

[IETF RFC 4512, 2006]:

Internet Engineering Task Force (on-line) <http://tools.ietf.org>, Request for Comment 4512, "Lightweight Directory Access Protocol (LDAP): Directory Information Models", K. Zeilenga, at <http://tools.ietf.org/html/rfc4512>, June 2006, viewed 19 May 2011.

[IETF RFC 4513, 2006]:

Internet Engineering Task Force (on-line) <http://tools.ietf.org>, Request for Comment 4513, "Lightweight Directory Access Protocol (LDAP): Authentication Methods and Security Mechanisms", R. Harrison, Ed., at <http://www.ietf.org/rfc/rfc4513.txt>, June 2006, viewed 19 May 2011.

[IETF RFC 4514, 2006]:

Internet Engineering Task Force (on-line) <http://tools.ietf.org>, Request for Comment 4514, "Lightweight Directory Access Protocol (LDAP): String Representation of Distinguished Names", K. Zeilenga, at <http://tools.ietf.org/html/rfc4514>, June 2006, viewed 19 May 2011.

[IETF RFC 4515, 2006]:

Internet Engineering Task Force (on-line) <http://tools.ietf.org>, Request for Comment 4515, "Lightweight Directory Access Protocol (LDAP): String Representation of Search Filters", M. Smith, T. Howes, at <http://tools.ietf.org/html/rfc4515>, June 2006, viewed 19 May 2011.

[IETF RFC 4516, 2006]:

Internet Engineering Task Force (on-line) <http://tools.ietf.org>, Request for Comment 4516, "Lightweight Directory Access Protocol (LDAP): Uniform Resource Locator", M. Smith, T. Howes, at <http://tools.ietf.org/html/rfc4516>, June 2006, viewed 19 May 2011.

[IETF RFC 4517, 2006]:

Internet Engineering Task Force (on-line) <http://tools.ietf.org>, Request for Comment 4517, "Lightweight Directory Access Protocol (LDAP): Syntaxes and Matching Rules", S. Legg, at <http://tools.ietf.org/html/rfc4517>, June 2006, viewed 19 May 2011.

[IETF RFC 4518, 2006]:

Internet Engineering Task Force (on-line) <http://tools.ietf.org>, Request for Comment 4518, "Lightweight Directory Access Protocol (LDAP): Internationalized String Preparation", K. Zeilenga, at <http://tools.ietf.org/html/rfc4518>, June 2006, viewed 19 May 2011.

[IETF RFC 4519, 2006]:

Internet Engineering Task Force (on-line) <http://tools.ietf.org>, Request for Comment 4519, "Lightweight Directory Access Protocol (LDAP): Schema for User Applications", A. Sciberras, Ed., at <http://tools.ietf.org/html/rfc4519>, June 2007, viewed 19 May 2011.

[NAC EAPC(AC/322-SC/1)N(2009)0015 (INV), 2009]:

North Atlantic Council/Euro-Atlantic Partnership Council Notice EAPC(AC/322-SC/1)N(2009)0015 (INV), "Core Enterprise Services Framework v1.2", NAC, Brussels, Belgium, 30 Apr 2009 (NATO/EAPC Unclassified).

[NC3A RD-3186, 2011]:

NATO Consultation, Command and Control Agency Reference Document 3186, "Collaboration Service Interface Profile Proposal", NC3A CES Team, NC3A, The Hague, Netherlands, unpublished draft dated June 2011 (NATO Unclassified).

[NCIA TR/2012/CPW007253/02, 2012]:

NATO Communications and Information Agency Technical Report 2012/CPW007253/02, "Security Services Service Interface Profile Proposal", R. Fiske, M. Lehmann, R. Malewicz, L. Schenkels, D. Gujral, NCIA, The Hague, Netherlands, October 2012 (NATO Unclassified).

[OASIS DSML, 2002]:

Organization for the Advancement of Structured Information Standards (on-line), <http://www.oasis-open.org>, Directory Services Markup Language v2.0, Organization for the Advancement of Structured Information Standards, April 2002 at <http://www.oasis-open.org/committees/dsml/docs/DSMLv2.doc> viewed 19 May 2011.

[OASIS SPML, 2006]:

Organization for the Advancement of Structured Information Standards (on-line), <http://www.oasis-open.org>, Service Provisioning Markup Language v2.0, Organization for the Advancement of Structured Information Standards, April 2006 at <http://www.oasis-open.org/committees/download.php/17708/pstc-spml-2.0-os.zip> viewed 19 May 2011.

5 ABBREVIATIONS

ARH	Alliance replication hub
ASN	Abstract syntax notation
CES	Core Enterprise Services
CSV	Comma-separated value
ITU	International Telecommunication Union
LDAP	Lightweight directory access protocol
LDIF	LDAP data interchange format
NEID	NATO enterprise identifier
NNEC	NATO Network Enabled Capability
RDN	Relative distinguished name
RFC	Request for comments
SASL	Simple authentication and security layer
SIP	Service interface profile
SQL	Structured query language
SSO	Single sign-on
TLS	Transport layer security
WSDL	Web services description language
XML	Extensible markup language

ANNEX 1 – LDAP REPRESENTATION OF THE BASE DIRECTORY SCHEMA

The following is a complete ACP 133(C) LDAP *directory schema* containing all the attributes and object classes that may be found within an ACP 133(C) compliant DIB.

```
# ACP 133(C) LDAP Schema derived from commented X.500 ASN.1 Module
# Developed by NC3A, The Hague, 28th July 2009 and updated November 2010.
#
```

```
objectclass (2.5.6.1
    NAME 'alias'
    SUP top
    STRUCTURAL
    MUST ( aliasedObjectName ) )

objectclass (2.5.6.2
    NAME 'country'
    SUP top
    STRUCTURAL
    MUST ( c )
    MAY ( searchGuide $
        description ) )

objectclass (2.5.6.19
    NAME 'cRLDistributionPoint'
    SUP top
    STRUCTURAL
    MUST ( cn )
    MAY ( certificateRevocationList $
        authorityRevocationList $
        deltaRevocationList ) )

objectclass (2.5.6.14
    NAME 'device'
    SUP top
    STRUCTURAL
    MUST ( cn )
    MAY ( serialNumber $
        seeAlso $
        owner $
        ou $
        o $
        l $
        description ) )

objectclass (2.5.6.9
    NAME 'groupOfNames'
    SUP top
    STRUCTURAL
    MUST ( member $
        cn )
    MAY ( businessCategory $
        seeAlso $
        owner $
        ou $
        o $
        description ) )

objectclass (2.16.840.1.113730.3.2.2
    NAME 'inetOrgPerson'
    DESC 'RFC2798: Internet Organizational Person'
    SUP organizationalPerson
    STRUCTURAL
    MAY ( audio $
        businessCategory $
        carLicense $
        departmentNumber $
        displayName $
        employeeNumber $
```



```

employeeType $
givenName $
homePhone $
homePostalAddress $
initials $
jpegPhoto $
labeledURI $
mail $
manager $
mobile $
o $
pager $
photo $
preferredLanguage $
roomNumber $
secretary $
uid $
userCertificate $
x500uniqueIdentifier $
userSMIMECertificate $
userPKCS12 ) )

```

```

objectclass (2.5.6.3
NAME 'locality'
SUP top
STRUCTURAL
MAY ( street $
      seeAlso $
      searchGuide $
      st $
      l $
      description ) )

```

```

objectclass (2.5.6.4
NAME 'organization'
SUP top
STRUCTURAL
MUST ( o )
MAY ( userPassword $
      searchGuide $
      seeAlso $
      businessCategory $
      x121Address $
      registeredAddress $
      destinationIndicator $
      preferredDeliveryMethod $
      telexNumber $
      teletexTerminalIdentifier $
      telephoneNumber $
      internationalISDNNumber $
      facsimileTelephoneNumber $
      street $
      postOfficeBox $
      postalCode $
      postalAddress $
      physicalDeliveryOfficeName $
      st $
      l $
      description ) )

```

```

objectclass (2.5.6.7
NAME 'organizationalPerson'
SUP person
STRUCTURAL
MAY ( title $
      x121Address $
      registeredAddress $
      destinationIndicator $
      preferredDeliveryMethod $
      telexNumber $
      teletexTerminalIdentifier $
      telephoneNumber $
      internationalISDNNumber $

```

```

        facsimileTelephoneNumber $
        street $
        postOfficeBox $
        postalCode $
        postalAddress $
        physicalDeliveryOfficeName $
        ou $
        st $
        l $
    ) )

objectclass (2.5.6.8
    NAME 'organizationalRole'
    SUP top
    STRUCTURAL
    MUST ( cn )
    MAY ( x121Address $
        registeredAddress $
        destinationIndicator $
        preferredDeliveryMethod $
        telexNumber $
        teletexTerminalIdentifier $
        telephoneNumber $
        internationalISDNNumber $
        facsimileTelephoneNumber $
        seeAlso $
        roleOccupant $
        preferredDeliveryMethod $
        street $
        postOfficeBox $
        postalCode $
        postalAddress $
        physicalDeliveryOfficeName $
        ou $
        st $
        l $
        description ) )

objectclass (2.5.6.5
    NAME 'organizationalUnit'
    SUP top
    STRUCTURAL
    MUST ( ou )
    MAY ( userPassword $
        searchGuide $
        seeAlso $
        businessCategory $
        x121Address $
        registeredAddress $
        destinationIndicator $
        preferredDeliveryMethod $
        telexNumber $
        teletexTerminalIdentifier $
        telephoneNumber $
        internationalISDNNumber $
        facsimileTelephoneNumber $
        street $
        postOfficeBox $
        postalCode $
        postalAddress $
        physicalDeliveryOfficeName $
        st $
        l $
        description ) )

objectclass (2.5.6.6
    NAME 'person'
    SUP top
    STRUCTURAL
    MUST ( sn $
        cn )
    MAY ( userPassword $
        telephoneNumber $
        seeAlso $

```

```

description ) )

objectclass (2.5.6.22
  NAME 'pkiCA'
  DESC 'X.509 PKI Certificate Authority'
  SUP top
  AUXILIARY
  MAY ( cACertificate $
        certificateRevocationList $
        authorityRevocationList $
        crossCertificatePair ) )

objectclass (2.5.6.21
  NAME 'pkiUser'
  DESC 'X.509 PKI User'
  SUP top
  AUXILIARY
  MAY ( userCertificate ) )

objectclass (2.5.6.0
  NAME 'top'
  ABSTRACT
  MUST objectClass)

objectclass (2.16.840.1.101.2.2.3.81
  NAME 'aCPDistributionCodesHandled'
  DESC 'Associate distribution codes with an entry'
  SUP top
  AUXILIARY
  MAY (distributionCodeAction $
        distributionCodeInfo $
        distributionExemptAction $
        distributionExemptInfo $
        distributionKeywordAction $
        distributionKeywordInfo))

objectclass (2.16.840.1.101.2.2.3.102
  NAME 'aCPEntryAdmin'
  DESC 'Associate standard information with an entry'
  SUP top
  AUXILIARY
  MAY (aCPEID $
        aCPEntryCreationDate $
        aCPEntryModificationDate $
        aCPEntryType $
        aCPEntryUniqueId))

objectclass (2.16.840.1.101.2.2.3.104
  NAME 'aCPEntryCharacteristics'
  DESC 'Associates the functions, tasks, COIs and CSSs with an entry'
  SUP top
  AUXILIARY
  MAY (aCPCOI $
        aCPFunctionalDescription $
        aCPPublishTo $
        aCPSvcApps))

objectclass (2.16.840.1.101.2.2.3.82
  NAME 'aCPMhsCapabilitiesInformation'
  DESC 'Associates the message capabilities information with an entry'
  SUP top
  AUXILIARY
  MAY (active $
        emConCapability $
        emConState $
        fileTypeInfoCapability $
        maxMessageSize $
        minimize $
        msgProtocolInfoCapability $
        webAccessCapability))

objectclass (2.16.840.1.101.2.2.3.83
  NAME 'aCPOtherContactInformation'

```



```

DESC 'Associates additional contact information with an entry'
SUP top
AUXILIARY
MAY (mhsORAddresses $
    buildingName $
    mobile $
    pager $
    roomNumber $
    aCPPreferredDelivery $
    mailDomains $
    militaryFacsimileNumber $
    militaryIPPhoneNumber $
    militaryTelephoneNumber $
    proprietaryMailboxes $
    secureFacsimileNumber $
    secureTelephoneNumber))

objectclass (2.16.840.1.101.2.2.3.70
    NAME 'aCPAddressList'
    DESC 'A group of users that are named and addressed as a group for messaging
purposes'
    SUP top
    MUST (cn)
    MAY (mhsDLSubmitPermissions $
        mhsDLRelatedLists $
        businessCategory $
        description $
        o $
        ou $
        owner $
        seeAlso $
        aLExemptedAddressProcessor $
        mail $
        actionAddressees $
        aliasPointer $
        alternateRecipient $
        aLType $
        member $
        copyMember $
        guard $
        infoAddressees $
        listPointer $
        nationality $
        remarks $
        effectiveDate $
        expirationDate ))

nameform (2.16.840.1.101.2.2.4.44
    NAME 'aCPAddressListNameForm'
    OC aCPAddressList
    MUST ( commonName ))

objectclass (2.16.840.1.101.2.2.3.71
    NAME 'aCPAliasCommonName'
    DESC 'An alias that can be named with a cn attribute value'
    SUP alias
    MUST ( cn )
    MAY (effectiveDate $
        expirationDate))

nameform (2.16.840.1.101.2.2.4.45
    NAME 'aCPAliasCommonNameNameForm'
    OC aCPAliasCommonName
    MUST ( cn ))

objectclass (2.16.840.1.101.2.2.3.72
    NAME 'aCPAliasOrganizationalUnit'
    DESC 'An alias that can be named with an ou attribute value'
    SUP alias
    MUST ( ou )
    MAY (effectiveDate $
        expirationDate))

```

```

nameform (2.16.840.1.101.2.2.4.46
  NAME 'aCPAliasOrganizationalUnitNameForm'
  OC aCPAliasOrganizationalUnit
  MUST ( ou ))

objectclass (2.16.840.1.101.2.2.3.73
  NAME 'aCPDevice'
  DESC 'A physical unit which can communicate or store information, such as a
modem, printer, etc'
  SUP device
  MAY (aliasPointer $
    effectiveDate $
    expirationDate))

nameform (2.16.840.1.101.2.2.4.47
  NAME 'aCPDeviceNameForm'
  OC aCPDevice
  MUST ( cn ))

objectclass (2.16.840.1.101.2.2.3.74
  NAME 'aCPDistributionCodeDescription'
  DESC 'A registered distribution code and its description'
  SUP top
  MUST ( cn )
  MAY (description $
    aliasPointer $
    effectiveDate $
    expirationDate))

nameform (2.16.840.1.101.2.2.4.48
  NAME 'aCPDistributionCodeDescriptionNameForm'
  OC aCPDistributionCodeDescription
  MUST ( cn ))

objectclass (2.16.840.1.101.2.2.3.75
  NAME 'aCPGroupOfNames'
  DESC 'A static group of entries or other groups of names, often used in
constructing ACLs'
  SUP groupOfNames
  MAY (aliasPointer $
    effectiveDate $
    expirationDate))

nameform (2.16.840.1.101.2.2.4.49
  NAME 'aCPGroupOfNamesNameForm'
  OC aCPGroupOfNames
  MUST ( cn ))

objectclass (2.16.840.1.101.2.2.3.76
  NAME 'aCPLocality'
  DESC 'An ACP133 locality'
  SUP locality
  MAY (aliasPointer $
    effectiveDate $
    expirationDate))

nameform (2.16.840.1.101.2.2.4.50
  NAME 'aCPLocalityNameForm'
  OC aCPLocality
  MUST (l $
    st))

objectclass (2.16.840.1.101.2.2.3.77
  NAME 'aCPOrganization'
  DESC 'An ACP133 Organisation'
  SUP organization
  MAY (dnQualifier $
    aCPLegacyFormat $
    aliasPointer $
    effectiveDate $
    expirationDate))

nameform (2.16.840.1.101.2.2.4.51

```

NAME 'aCPOrganizationNameForm'
MUST (o))

```
objectclass (2.16.840.1.101.2.2.3.103
  NAME 'aCPOrganizationalLocation'
  DESC 'An entry containing information about a site or other location'
  SUP top
  MUST(cn $
    1 )
  MAY (businessCategory $
    description $
    seeAlso $
    jpegPhoto $
    aCPDirectionsTo $
    aCPDutyOfficer $
    aCPLatitude $
    aCPLocationMap $
    aCPLongitude $
    aliasPointer $
    nationality $
    st $
    streetAddress $
    physicalDeliveryOfficeName $
    postalAddress $
    postalCode $
    postOfficeBox $
    facsimileTelephoneNumber $
    internationalISDNNumber $
    telephoneNumber $
    telexNumber $
    preferredDeliveryMethod $
    destinationIndicator $
    registeredAddress $
    x121address $
    effectiveDate $
    expirationDate))
```

```
nameform (2.16.840.1.101.2.2.4.52
  NAME 'aCPOrganizationalLocationNameForm'
  OC aCPOrganizationalLocation
  MUST ( cn ))
```

```
objectclass (2.16.840.1.101.2.2.3.78
  NAME 'aCPOrganizationalPerson'
  DESC 'An entry containing information representing an individual as a member of
an organization'
  SUP inetOrgPerson
  MAY (dnQualifier $
    clearance $
    aCPCitizenship $
    aCPLegacyFormat $
    aliasPointer $
    alternateRecipient $
    coalitionGrade $
    deployed $
    garrison $
    guard $
    listPointer $
    nationality $
    positionNumber $
    rank $
    serviceNumber $
    effectiveDate $
    expirationDate))
```

```
nameform (2.16.840.1.101.2.2.4.53
  NAME 'aCPOrganizationalPersonNameForm'
  OC aCPOrganizationalPerson
  MUST ( cn ))
```

```
objectclass (2.16.840.1.101.2.2.3.79
  NAME 'aCPOrganizationalRole'
  DESC 'An entry containing information representing a role or function which is
```



```

performed by one or more persons'
  SUP organizationalRole
  MAY (businessCategory $
    dnQualifier $
    clearance $
    mail $
    aCPCitizenship $
    aCPLegacyFormat $
    aCPRoleInformation $
    aliasPointer $
    alternateRecipient $
    deployed $
    garrison $
    guard $
    listPointer $
    nationality $
    effectiveDate $
    expirationDate ))

nameform (2.16.840.1.101.2.2.4.54
  NAME 'aCPOrganizationalRoleNameForm'
  OC aCPOrganizationalRole
  MUST ( cn ))

objectclass (2.16.840.1.101.2.2.3.80
  NAME 'aCPOrganizationalUnit'
  DESC 'An entry representing a suborganization'
  SUP organizationalUnit
  MAY (dnQualifier $
    clearance $
    mail $
    aCPLegacyFormat $
    aliasPointer $
    alternateRecipient $
    associatedPLA $
    deployed $
    garrison $
    guard $
    listPointer $
    nationality $
    effectiveDate $
    expirationDate))

nameform (2.16.840.1.101.2.2.4.55
  NAME 'aCPOrganizationalUnitNameForm'
  OC aCPOrganizationalUnit
  MUST ( ou ))

objectclass (2.16.840.1.101.2.2.3.86
  NAME 'aCPSecurePKIUser'
  DESC 'Allows PKI certificates to be associated with an entry'
  SUP top
  AUXILIARY
  MAY (attributeCertificateAttribute $
    userCertificate $
    supportedAlgorithms))

objectclass (2.16.840.1.101.2.2.3.85
  NAME 'aCPCRLDistributionPoint'
  DESC 'An entry used for holding a CRL that is a subset of the complete CRL.'
  SUP cRLDistributionPoint
  MAY (aliasPointer $
    effectiveDate $
    expirationDate))

nameform (2.16.840.1.101.2.2.4.56
  NAME 'aCPCRLDistributionPointNameForm'
  OC aCPCRLDistributionPoint
  MUST ( cn ))

objectclass (2.16.840.1.101.2.2.3.98
  NAME 'aCPPlaACPI27'
  DESC 'Common general service (GENSER) PLA attributes'

```

```

SUP top
AUXILIARY
MUST plaNameACP127
MAY (community $
    nationality $
    publish $
    remarks $
    serviceOrAgency $
    effectiveDate $
    expirationDate))

objectclass (2.16.840.1.101.2.2.3.99
    NAME 'aCPPlaData'
    DESC 'Common special intelligence (SI) PLA attributes'
    SUP top
    AUXILIARY
    MAY (description $
        community $
        effectiveDate $
        expirationDate))

objectclass (2.16.840.1.101.2.2.3.84
    NAME 'aCPPlaUser'
    DESC 'Associates the PLA directory entry and optionally the routing information,
with an entry'
    SUP top
    AUXILIARY
    MUST plaNameACP127
    MAY (alternatePLAName $
        rI $
        rIInfo))

objectclass (2.16.840.1.101.2.2.3.87
    NAME 'aCPAltSpellingACP127'
    DESC 'An alternate spelling for a PLA'
    SUP top
    MUST (plaReplace $
        primarySpellingACP127))

nameform (2.16.840.1.101.2.2.4.57
    NAME 'aCPAltSpellingACP127NameForm'
    OC aCPAltSpellingACP127
    MUST ( plaNameACP127 ))

objectclass (2.16.840.1.101.2.2.3.88
    NAME 'aCPCadACP127'
    DESC 'A collective address designator (CAD) used to represent an ACP127/JANAP128
distribution list'
    SUP top
    MUST ( cognizantAuthority )
    MAY (associatedAL $
        entryClassification $
        recapDueDate $
        rIInfo))

nameform (2.16.840.1.101.2.2.4.58
    NAME 'aCPCadACP127NameForm'
    OC aCPCadACP127
    MUST ( plaNameACP127 ))

objectclass (2.16.840.1.101.2.2.3.89
    NAME 'aCPDSSCSPLA'
    DESC 'An intelligence community (IC) PLA organisation'
    SUP top
    MUST ( rI )
    MAY (l $
        adminConversion $
        associatedOrganization $
        sigad $
        usdConversion))

nameform (2.16.840.1.101.2.2.4.59
    NAME 'aCPDSSCSPLANameForm'

```

```

OC aCPDSSCSPLA
MUST ( plaNameACP127 ))

objectclass (2.16.840.1.101.2.2.3.90
  NAME 'aCPOrgACP127'
  DESC 'A single ACP127/JANAP128 messaging user'
  SUP top
  MAY (c $
    l $
    st $
    accountingCode $
    associatedOrganization $
    dualRoute $
    entryClassification $
    longTitle $
    minimize $
    minimizeOverride $
    nameClassification $
    rI $
    rIInfo $
    section $
    tARE))

nameform (2.16.840.1.101.2.2.4.60
  NAME 'aCPOrgACP127NameForm'
  OC aCPOrgACP127
  MUST ( plaNameACP127 ))

objectclass (2.16.840.1.101.2.2.3.91
  NAME 'aCPPLACollectiveACP127'
  DESC 'An address indicator group (AIG) used to represent an ACP127/JANAP128
distribution list'
  SUP top
  MUST cognizantAuthority
  MAY (description $
    actionAddressees $
    allowableOriginators $
    associatedAL $
    entryClassification $
    infoAddressees $
    lastRecapDate $
    recapDueDate))

nameform (2.16.840.1.101.2.2.4.61
  NAME 'aCPPLACollectiveACP127NameForm'
  OC aCPPLACollectiveACP127
  MUST ( plaNameACP127 ))

objectclass (2.16.840.1.101.2.2.3.92
  NAME 'aCPRoutingIndicator'
  DESC 'A routing indicator'
  SUP top
  MUST rI
  MAY (mhsMaximumContentLength $
    lmf $
    nationality $
    publish $
    rIClassification $
    sHD $
    tCC $
    transferStation $
    tRC ))

nameform (2.16.840.1.101.2.2.4.62
  NAME 'aCPRoutingIndicatorNameForm'
  OC aCPRoutingIndicator
  MUST ( rI ))

objectclass (2.16.840.1.101.2.2.3.93
  NAME 'aCPSigIntPLA'
  DESC 'A sensitive signal intelligence (SIGINT) PLA'
  SUP top
  MUST sigad

```

```

MAY (1 $
    nationality $
    publish $
    remarks $
    rI $
    shortTitle))

nameform (2.16.840.1.101.2.2.4.63
    NAME 'aCPSigIntPLANameForm'
    OC aCPSigIntPLA
    MUST ( sigad ))

objectclass (2.16.840.1.101.2.2.3.94
    NAME 'aCPSIPLA'
    DESC 'A single special intelligence (SO) messaging user'
    SUP top
    MUST (sigad $
        longTitle )
    MAY (1 $
        nationality $
        publish $
        remarks $
        rI $
        shortTitle))

nameform (2.16.840.1.101.2.2.4.64
    NAME 'aCPSIPLANameForm'
    OC aCPSIPLA
    MUST ( longTitle ))

objectclass (2.16.840.1.101.2.2.3.95
    NAME 'aCPSpotPLA'
    DESC 'A special products distribution list'
    SUP top
    MUST spot
    MAY (mhsDLSubmitPermissions $
        actionAddressees $
        additionalAddressees $
        additionalSecondPartyAddressees $
        remarks $
        secondPartyAddressees))

nameform (2.16.840.1.101.2.2.4.65
    NAME 'aCPSpotPLANameForm'
    OC aCPSpotPLA
    MUST ( spot ))

objectclass (2.16.840.1.101.2.2.3.96
    NAME 'aCPTaskForceACP127'
    DESC 'A ACP127/JANAP128 task force distribution list'
    SUP top
    MUST (cognizantAuthority $
        lastRecapDate $
        recapDueDate )
    MAY (associatedAL $
        entryClassification $
        plaAddressees))

nameform (2.16.840.1.101.2.2.4.66
    NAME 'aCPTaskForceACP127NameForm'
    OC aCPTaskForceACP127
    MUST ( rI ))

objectclass (2.16.840.1.101.2.2.3.97
    NAME 'aCPTenantACP127'
    DESC 'A tenant PLA'
    SUP top
    MUST hostOrgACP127
    MAY (entryClassification $
        tARE ))

nameform (2.16.840.1.101.2.2.4.67
    NAME 'aCPTenantACP127NameForm'

```



```

OC aCPTenantACP127
MUST ( plaNameACP127 ))

attributetype ( 2.16.840.1.101.2.2.1.53
  NAME 'accountingCode'
  EQUALITY caseIgnoreMatch
  SUBSTR caseIgnoreSubstringsMatch
  SYNTAX 1.3.6.1.4.1.1466.115.121.1.44 )

attributetype ( 2.16.840.1.101.2.2.1.178
  NAME 'aCPCitizenship'
  DESC 'The citizenship of the entry (ISO 3166-3)'
  EQUALITY caseIgnoreMatch
  SUBSTR caseIgnoreSubstringsMatch
  SYNTAX 1.3.6.1.4.1.1466.115.121.1.44 )

attributetype ( 2.16.840.1.101.2.2.1.180
  NAME 'aCPCOI'
  DESC 'The communities of interest (COI) associated with the entry'
  EQUALITY caseIgnoreMatch
  SUBSTR caseIgnoreSubstringsMatch
  SYNTAX 1.3.6.1.4.1.1466.115.121.1.44 )

attributetype ( 2.16.840.1.101.2.2.1.183
  NAME 'aCPDirectionsTo'
  DESC 'The URI of a webpage containing details of the directions to reach the
location'
  EQUALITY caseIgnoreMatch
  SUBSTR caseIgnoreSubstringsMatch
  SYNTAX 1.3.6.1.4.1.1466.115.121.1.44 )

attributetype ( 2.16.840.1.101.2.2.1.184
  NAME 'aCPDutyOfficer'
  SUP distinguishedName )

attributetype ( 2.16.840.1.101.2.2.1.179
  NAME 'aCPEID'
  DESC 'A time-based, universally unique identifier (UUID) for the entry'
  EQUALITY caseIgnoreMatch
  SUBSTR caseIgnoreSubstringsMatch
  SINGLE-VALUE
  SYNTAX 1.3.6.1.4.1.1466.115.121.1.44 )

attributetype ( 2.16.840.1.101.2.2.1.174
  NAME 'aCPEntryCreationDate'
  DESC 'The date and time the entry was created'
  EQUALITY generalizedTimeMatch
  SINGLE-VALUE
  SYNTAX 1.3.6.1.4.1.1466.115.121.1.24 )

attributetype ( 2.16.840.1.101.2.2.1.175
  NAME 'aCPEntryModificationDate'
  DESC 'The date and time the entry was last modified'
  EQUALITY generalizedTimeMatch
  SINGLE-VALUE
  SYNTAX 1.3.6.1.4.1.1466.115.121.1.24 )

attributetype ( 2.16.840.1.101.2.2.1.176
  NAME 'aCPEntryType'
  DESC 'The type of entry, defined by the owning nation or organization'
  EQUALITY objectIdentifierMatch
  SINGLE-VALUE
  SYNTAX 1.3.6.1.4.1.1466.115.121.1.38 )

attributetype ( 2.16.840.1.101.2.2.1.177
  NAME 'aCPEntryUniqueId'
  DESC 'A unique identifier within the aCPEntryType, defined by the owning nation
or organization'
  EQUALITY integerMatch
  SINGLE-VALUE
  SYNTAX 1.3.6.1.4.1.1466.115.121.1.27 )

attributetype ( 2.16.840.1.101.2.2.1.172

```

```

NAME 'aCPFunctionalDescription'
DESC 'The function or task of the entry'
EQUALITY caseIgnoreMatch
SUBSTR caseIgnoreSubstringsMatch
SYNTAX 1.3.6.1.4.1.1466.115.121.1.44 )

attributetype ( 2.16.840.1.101.2.2.1.185
NAME 'aCPLatitude'
DESC 'The latitude ("Northings") of the location'
EQUALITY caseIgnoreMatch
SUBSTR caseIgnoreSubstringsMatch
SINGLE-VALUE
SYNTAX 1.3.6.1.4.1.1466.115.121.1.44 )

attributetype ( 2.16.840.1.101.2.2.1.142
NAME 'aCPLegacyFormat'
DESC 'The message format type for ACP127 delivery'
EQUALITY integerMatch
SINGLE-VALUE
SYNTAX 1.3.6.1.4.1.1466.115.121.1.27 )

attributetype ( 2.16.840.1.101.2.2.1.186
NAME 'aCPLocationMap'
DESC 'The URI of a web page containing a map of the location'
EQUALITY caseIgnoreMatch
SUBSTR caseIgnoreSubstringsMatch
SYNTAX 1.3.6.1.4.1.1466.115.121.1.44 )

attributetype ( 2.16.840.1.101.2.2.1.187
NAME 'aCPLongitude'
DESC 'The longitude ("Eastings") of the location'
EQUALITY caseIgnoreMatch
SUBSTR caseIgnoreSubstringsMatch
SINGLE-VALUE
SYNTAX 1.3.6.1.4.1.1466.115.121.1.44 )

attributetype ( 2.16.840.1.101.2.2.1.108
NAME 'aCPPreferredDelivery'
DESC 'The message system that a user prefers for message delivery'
EQUALITY integerMatch
SINGLE-VALUE
SYNTAX 1.3.6.1.4.1.1466.115.121.1.27 )

attributetype ( 2.16.840.1.101.2.2.1.181
NAME 'aCPPublishTo'
DESC 'The domains, communities or deployments to which the entry should be
published'
EQUALITY caseIgnoreMatch
SUBSTR caseIgnoreSubstringsMatch
SYNTAX 1.3.6.1.4.1.1466.115.121.1.44 )

attributetype ( 2.16.840.1.101.2.2.1.158
NAME 'aCPRoleInformation'
DESC 'An informal mapping to simplify the access to organizational person
entries related to this role'
EQUALITY caseIgnoreMatch
SUBSTR caseIgnoreSubstringsMatch
SYNTAX 1.3.6.1.4.1.1466.115.121.1.15 )

attributetype ( 2.16.840.1.101.2.2.1.182
NAME 'aCPSvcApps'
DESC 'The centralized applications to which the entry has access'
EQUALITY caseIgnoreMatch
SUBSTR caseIgnoreSubstringsMatch
SYNTAX 1.3.6.1.4.1.1466.115.121.1.44 )

attributetype ( 2.16.840.1.101.2.2.1.109
NAME 'aCPTelephoneFaxNumber'
DESC 'A supertype for defining other fax/telephone number attributes'
EQUALITY telephoneNumberMatch
SUBSTR telephoneNumberSubstringsMatch
SYNTAX 1.3.6.1.4.1.1466.115.121.1.50 )

```

```

attributetype ( 2.16.840.1.101.2.2.1.46
  NAME 'actionAddressees'
  DESC 'The addressees who are expected to take appropriate action on the
message'
  EQUALITY caseIgnoreMatch
  SUSBTR caseIgnoreSubstringsMatch
  SYNTAX 1.3.6.1.4.1.1466.115.121.1.44 )

attributetype ( 2.16.840.1.101.2.2.1.164
  NAME 'active'
  DESC 'Whether the tactical entry is active or inactive'
  EQUALITY booleanMatch
  SINGLE-VALUE
  SYNTAX 1.3.6.1.4.1.1466.115.121.1.7 )

attributetype ( 2.16.840.1.101.2.2.1.47
  NAME 'additionalAddressees'
  DESC 'The additional addressees who are expected to take appropriate action on
the message under circumstances identified in the remarks attribute'
  EQUALITY caseIgnoreMatch
  SUSBTR caseIgnoreSubstringsMatch
  SYNTAX 1.3.6.1.4.1.1466.115.121.1.44 )

attributetype ( 2.16.840.1.101.2.2.1.48
  NAME 'additionalSecondPartyAddressees'
  DESC 'The additional second party addressees who are expected to take
appropriate action on messages under circumstances identified in the remarks attribute'
  EQUALITY caseIgnoreMatch
  SUSBTR caseIgnoreSubstringsMatch
  SYNTAX 1.3.6.1.4.1.1466.115.121.1.44 )

attributetype ( 2.16.840.1.101.2.2.1.143
  NAME 'adminConversion'
  DESC 'An abbreviation of the organization's administrative title as an
administrative message address'
  EQUALITY caseIgnoreMatch
  SUSBTR caseIgnoreSubstringsMatch
  SYNTAX 1.3.6.1.4.1.1466.115.121.1.15 )

attributetype ( 2.16.840.1.101.2.1.5.47
  NAME 'aLExemptedAddressProcessor'
  DESC 'The X.400 O/R Name of the address list's exempted address processor'
  EQUALITY caseIgnoreMatch
  SUSBTR caseIgnoreSubstringsMatch
  SINGLE-VALUE
  SYNTAX 2.16.840.1.101.2.2.2.15)

attributetype (2.5.4.1
  NAME ('aliasedObjectName' 'aliasedEntryName')
  EQUALITY distinguishedNameMatch
  SYNTAX 1.3.6.1.4.1.1466.115.121.1.12
  SINGLE-VALUE)

attributetype ( 2.16.840.1.101.2.2.1.49
  NAME 'aliasPointer'
  DESC 'The entries that may need to be modified if this entry is modified'
  SUP distinguishedName)

attributetype ( 2.16.840.1.101.2.2.1.50
  NAME 'allowableOriginators'
  DESC 'The name of an ACP127/JANAP128 collective that contains the list of PLAs
that are allowed to originate message to this list'
  EQUALITY caseIgnoreMatch
  SUSBTR caseIgnoreSubstringsMatch
  SYNTAX 1.3.6.1.4.1.1466.115.121.1.44)

attributetype ( 2.16.840.1.101.2.2.1.173
  NAME 'alternatePLAName'
  DESC 'An alternate plain language address'
  EQUALITY caseIgnoreMatch
  SUSBTR caseIgnoreSubstringsMatch
  SYNTAX 1.3.6.1.4.1.1466.115.121.1.44)

```



```

attributetype ( 2.16.840.1.101.2.2.1.3
    NAME 'alternateRecipient'
    DESC 'An X.400 alternate recipient for the messaging user'
    SUP distinguishedName )

attributetype ( 2.16.840.1.101.2.2.1.112
    NAME 'aLType'
    DESC 'The type of the address list'
    EQUALITY integerMatch
    SINGLE-VALUE
    SYNTAX 1.3.6.1.4.1.1466.115.121.1.27)

attributetype ( 2.16.840.1.101.2.2.1.113
    NAME 'associatedAL'
    DESC 'The address list entry which replaces the ACP127/JANAP128 Task Force PLA'
    SUP distinguishedName )

attributetype ( 2.16.840.1.101.2.2.1.4
    NAME 'associatedOrganization'
    DESC 'The organizational unit entry which represents the same organizational
messaging entity'
    SUP distinguishedName )

attributetype ( 2.16.840.1.101.2.2.1.6
    NAME 'associatedPLA'
    DESC 'The ACP127/JANAP128 entry which represents the same the same messaging
entity'
    SUP distinguishedName )

attributetype ( 2.5.4.58
    NAME 'attributeCertificateAttribute'
    DESC 'X.509 attribute certificate attribute'
    EQUALITY octetStringMatch
    SYNTAX 1.3.6.1.4.1.1466.115.121.1.40)

attributetype (0.9.2342.19200300.100.1.55
    NAME 'audio'
    EQUALITY octetStringMatch
    SYNTAX 1.3.6.1.4.1.1466.115.121.1.40 )

attributetype (2.5.4.38
    NAME 'authorityRevocationList'
    SYNTAX 1.3.6.1.4.1.1466.115.121.1.9 )

attributetype (0.9.2342.19200300.100.1.48
    NAME 'buildingName'
    EQUALITY caseIgnoreMatch
    SUBSTR caseIgnoreSubstringsMatch
    SYNTAX 1.3.6.1.4.1.1466.115.121.1.15{256} )

attributetype ( 2.5.4.15
    NAME 'businessCategory'
    EQUALITY caseIgnoreMatch
    SUBSTR caseIgnoreSubstringsMatch
    SYNTAX 1.3.6.1.4.1.1466.115.121.1.15{128} )

attributetype (2.5.4.37
    NAME 'cACertificate'
    EQUALITY certificateExactMatch
    SYNTAX 1.3.6.1.4.1.1466.115.121.1.8 )

attributetype (2.16.840.1.113730.3.1.1
    NAME 'carLicense'
    DESC 'RFC2798: vehicle license or registration plate'
    EQUALITY caseIgnoreMatch
    SUBSTR caseIgnoreSubstringsMatch
    SYNTAX 1.3.6.1.4.1.1466.115.121.1.15 )

attributetype (2.5.4.39
    NAME 'certificateRevocationList'
    SYNTAX 1.3.6.1.4.1.1466.115.121.1.9 )

attributetype(2.5.4.55

```



```

NAME 'clearance'
EQUALITY octetStringMatch
SYNTAX 1.3.6.1.4.1.1466.115.121.1.40 )

attributetype ( 2.16.840.1.101.2.2.1.159
NAME 'coalitionGrade'
DESC 'The NATO rank from STANAG 2166 or an applicable civil grade-code'
EQUALITY caseIgnoreMatch
SUBSTR caseIgnoreSubstringsMatch
SYNTAX 1.3.6.1.4.1.1466.115.121.1.15)

attributetype ( 2.16.840.1.101.2.2.1.51
NAME 'cognizantAuthority'
DESC 'The administrator of the ACPI27/JANAP128 collective'
EQUALITY caseIgnoreMatch
SUBSTR caseIgnoreSubstringsMatch
SINGLE-VALUE
SYNTAX 1.3.6.1.4.1.1466.115.121.1.44)

attributetype (2.5.4.3
NAME ( 'cn' 'commonName' )
SUP name )

attributetype ( 2.16.840.1.101.2.2.1.52
NAME 'community'
DESC 'The community, GENSER, SI or both, to which the entry belongs'
EQUALITY integerMatch
SINGLE-VALUE
SYNTAX 1.3.6.1.4.1.1466.115.121.1.27)

attributetype ( 2.16.840.1.101.2.2.1.114
NAME 'copyMember'
DESC 'The members who receive the message for information purposes (no action
required)'
SUP member )

attributetype (2.5.4.6
NAME ( 'c' 'countryName' )
SUP name
SINGLE-VALUE )

attributetype (2.5.4.40
NAME 'crossCertificatePair'
SYNTAX 1.3.6.1.4.1.1466.115.121.1.10 )

attributetype (2.5.4.53
NAME 'deltaRevocationList'
SYNTAX 1.3.6.1.4.1.1466.115.121.1.9 )

attributetype (2.16.840.1.113730.3.1.2
NAME 'departmentNumber'
DESC 'RFC2798: identifies a department within an organization'
EQUALITY caseIgnoreMatch
SUBSTR caseIgnoreSubstringsMatch
SYNTAX 1.3.6.1.4.1.1466.115.121.1.15 )

attributetype ( 2.5.4.13
NAME 'description'
EQUALITY caseIgnoreMatch
SUBSTR caseIgnoreSubstringsMatch
SYNTAX 1.3.6.1.4.1.1466.115.121.1.15{1024} )

attributetype ( 2.16.840.1.101.2.2.1.139
NAME 'deployed'
DESC 'The entries that represent this entry in the field'
SUP distinguishedName )

attributetype (2.5.4.27
NAME 'destinationIndicator'
EQUALITY caseIgnoreMatch
SUBSTR caseIgnoreSubstringsMatch
SYNTAX 1.3.6.1.4.1.1466.115.121.1.44{128} )

```

```

attributetype (2.16.840.1.113730.3.1.241
  NAME 'displayName'
  DESC 'RFC2798: preferred name to be used when displaying entries'
  EQUALITY caseIgnoreMatch
  SUBSTR caseIgnoreSubstringsMatch
  SYNTAX 1.3.6.1.4.1.1466.115.121.1.15
  SINGLE-VALUE )

# Used for sub-typing
attributetype (2.5.4.49
  NAME 'distinguishedName'
  EQUALITY distinguishedNameMatch
  SYNTAX 1.3.6.1.4.1.1466.115.121.1.12 )

attributetype ( 2.16.840.1.101.2.2.1.104
  NAME 'distributionCodeAction'
  DESC 'The distribution codes (including SICs) for which an organization, person
or role handles messages for action'
  EQUALITY caseIgnoreMatch
  SUBSTR caseIgnoreSubstringsMatch
  SYNTAX 1.3.6.1.4.1.1466.115.121.1.44)

attributetype ( 2.16.840.1.101.2.2.1.105
  NAME 'distributionCodeInfo'
  DESC 'The distribution codes (including SICs) for which an organization, person
or role handles messages for information'
  EQUALITY caseIgnoreMatch
  SUBSTR caseIgnoreSubstringsMatch
  SYNTAX 1.3.6.1.4.1.1466.115.121.1.44)

attributetype ( 2.16.840.1.101.2.2.1.168
  NAME 'distributionExemptAction'
  DESC 'The distribution codes (including SICs) for which an organization, person
or role handles messages which are specifically exempted for action'
  EQUALITY caseIgnoreMatch
  SUBSTR caseIgnoreSubstringsMatch
  SYNTAX 1.3.6.1.4.1.1466.115.121.1.44)

attributetype ( 2.16.840.1.101.2.2.1.169
  NAME 'distributionExemptInfo'
  DESC 'The distribution codes (including SICs) for which an organization, person
or role handles messages which are specifically exempted for information'
  EQUALITY caseIgnoreMatch
  SUBSTR caseIgnoreSubstringsMatch
  SYNTAX 1.3.6.1.4.1.1466.115.121.1.44)

attributetype ( 2.16.840.1.101.2.2.1.170
  NAME 'distributionKeywordAction'
  EQUALITY caseIgnoreMatch
  DESC 'The keywords used for distribution for which an organization, person or
role handles messages for action'
  SUBSTR caseIgnoreSubstringsMatch
  SYNTAX 1.3.6.1.4.1.1466.115.121.1.44)

attributetype ( 2.16.840.1.101.2.2.1.171
  NAME 'distributionKeywordInfo'
  DESC 'The keywords used for distribution for which an organization, person or
role handles messages for information'
  EQUALITY caseIgnoreMatch
  SUBSTR caseIgnoreSubstringsMatch
  SYNTAX 1.3.6.1.4.1.1466.115.121.1.44)

attributetype (2.5.4.46
  NAME 'dnQualifier'
  EQUALITY caseIgnoreMatch
  ORDERING caseIgnoreOrderingMatch
  SUBSTR caseIgnoreSubstringsMatch
  SYNTAX 1.3.6.1.4.1.1466.115.121.1.44 )

attributetype ( 2.16.840.1.101.2.2.1.54
  NAME 'dualRoute'
  DESC 'Deliver messages for the organization to both the home and deployed
sites'

```

```

EQUALITY booleanMatch
SINGLE-VALUE
SYNTAX 1.3.6.1.4.1.1466.115.121.1.7)

attributetype ( 2.16.840.1.101.2.2.1.55
NAME 'effectiveDate'
DESC 'The date and time at which the directory entry becomes valid'
EQUALITY generalizedTimeMatch
SINGLE-VALUE
SYNTAX 1.3.6.1.4.1.1466.115.121.1.24 )

attributetype ( 2.16.840.1.101.2.2.1.165
NAME 'emConCapability'
DESC 'Whether the entry is capable of entering the emcon (radio silence) state'
EQUALITY booleanMatch
SINGLE-VALUE
SYNTAX 1.3.6.1.4.1.1466.115.121.1.7)

attributetype ( 2.16.840.1.101.2.2.1.166
NAME 'emConState'
DESC 'The emcon (radio silence) state'
EQUALITY integerMatch
SINGLE-VALUE
SYNTAX 1.3.6.1.4.1.1466.115.121.1.27)

attributetype (2.16.840.1.113730.3.1.3
NAME 'employeeNumber'
DESC 'RFC2798: numerically identifies an employee within an organization'
EQUALITY caseIgnoreMatch
SUBSTR caseIgnoreSubstringsMatch
SYNTAX 1.3.6.1.4.1.1466.115.121.1.15
SINGLE-VALUE )

attributetype (2.16.840.1.113730.3.1.4
NAME 'employeeType'
DESC 'RFC2798: type of employment for a person'
EQUALITY caseIgnoreMatch
SUBSTR caseIgnoreSubstringsMatch
SYNTAX 1.3.6.1.4.1.1466.115.121.1.15 )

attributetype ( 2.16.840.1.101.2.2.1.56
NAME 'entryClassification'
DESC 'The security classification of the entry'
EQUALITY integerMatch
SYNTAX 1.3.6.1.4.1.1466.115.121.1.27)

attributetype ( 2.16.840.1.101.2.2.1.57
NAME 'expirationDate'
DESC 'The date and time at which the directory entry becomes invalid'
EQUALITY generalizedTimeMatch
SINGLE-VALUE
SYNTAX 1.3.6.1.4.1.1466.115.121.1.24)

attributetype (2.5.4.23
NAME ( 'facsimileTelephoneNumber' 'fax' )
SYNTAX 1.3.6.1.4.1.1466.115.121.1.22 )

attributetype ( 2.16.840.1.101.2.2.1.161
NAME 'fileTypeInfoCapability'
DESC 'The types of attachments which are acceptable to the user associated with
the mailbox'
EQUALITY objectIdentifierMatch
SYNTAX 1.3.6.1.4.1.1466.115.121.1.38)

attributetype ( 2.16.840.1.101.2.2.1.140
NAME 'garrison'
DESC 'The entries that represent this entry in the garrison'
SUP distinguishedName )

attributetype (2.5.4.44
NAME 'generationQualifier'
DESC 'e.g. Jr or II.'
SUP name )

```

```

attributetype (2.5.4.42
  NAME ( 'givenName' 'gn' )
  SUP name )

attributetype ( 2.16.840.1.101.2.2.1.117
  NAME 'guard'
  DESC 'The entry of the guard gateway'
  SUP distinguishedName )

attributetype ( 0.9.2342.19200300.100.1.20
  NAME ( 'homePhone' 'homeTelephoneNumber' )
  EQUALITY telephoneNumberMatch
  SUBSTR telephoneNumberSubstringsMatch
  SYNTAX 1.3.6.1.4.1.1466.115.121.1.50 )

attributetype (0.9.2342.19200300.100.1.39
  NAME 'homePostalAddress'
  EQUALITY caseIgnoreListMatch
  SUBSTR caseIgnoreListSubstringsMatch
  SYNTAX 1.3.6.1.4.1.1466.115.121.1.41 )

attributetype ( 2.16.840.1.101.2.2.1.58
  NAME 'hostOrgACPI27'
  DESC 'The PLA for the organization which accepts traffic for a tenant'
  EQUALITY caseIgnoreMatch
  SUBSTR caseIgnoreSubstringsMatch
  SINGLE-VALUE
  SYNTAX 1.3.6.1.4.1.1466.115.121.1.44 )

attributetype ( 2.16.840.1.101.2.2.1.59
  NAME 'infoAddressees'
  DESC 'The addressees who receive the message for information'
  EQUALITY caseIgnoreMatch
  SUBSTR caseIgnoreSubstringsMatch
  SYNTAX 1.3.6.1.4.1.1466.115.121.1.44 )

attributetype (2.5.4.43
  NAME 'initials'
  DESC 'The initials attribute type contains the initials of some or all of an
individuals names, but not the surname(s).' )
  SUP name)

attributetype (2.5.4.25
  NAME 'internationalISDNNumber'
  EQUALITY numericStringMatch
  SUBSTR numericStringSubstringsMatch
  SYNTAX 1.3.6.1.4.1.1466.115.121.1.36{16} )

attributetype (0.9.2342.19200300.100.1.60
  NAME 'jpegPhoto'
  DESC 'a JPEG image'
  SYNTAX 1.3.6.1.4.1.1466.115.121.1.28 )

attributetype (1.3.6.1.4.1.250.1.57
  NAME 'labeledURI'
  DESC 'RFC2079: Uniform Resource Identifier with optional label'
  EQUALITY caseExactMatch
  SYNTAX 1.3.6.1.4.1.1466.115.121.1.15 )

attributetype ( 2.16.840.1.101.2.2.1.60
  NAME 'lastRecapDate'
  DESC 'The date and time when the list was last recapped or validated'
  EQUALITY generalizedTimeMatch
  SINGLE-VALUE
  SYNTAX 1.3.6.1.4.1.1466.115.121.1.24 )

attributetype ( 2.16.840.1.101.2.2.1.61
  NAME 'listPointer'
  DESC 'The address list entries that may need to be modified if this entry is
modified'
  SUP distinguishedName )

```



```

attributetype ( 2.16.840.1.101.2.2.1.62
    NAME 'lmf'
    DESC 'The lmf (Language and Media Format) that can be accepted between to two
communicating end-systems'
    EQUALITY caseIgnoreMatch
    SINGLE-VALUE
    SYNTAX 1.3.6.1.4.1.1466.115.121.1.44 )

attributetype (2.5.4.7
    NAME ( '1' 'localityName' )
    SUP name )

attributetype ( 2.16.840.1.101.2.2.1.63
    NAME 'longTitle'
    DESC 'The expanded form of an organization's PLA'
    EQUALITY caseIgnoreMatch
    SUBSTR caseIgnoreSubstringsMatch
    SINGLE-VALUE
    SYNTAX 1.3.6.1.4.1.1466.115.121.1.44 )

attributetype (0.9.2342.19200300.100.1.3
    NAME ( 'mail' 'rfc822Mailbox' )
    DESC 'RFC1274: RFC822 Mailbox'
    EQUALITY caseIgnoreIA5Match
    SUBSTR caseIgnoreIA5SubstringsMatch
    SYNTAX 1.3.6.1.4.1.1466.115.121.1.26{256} )

attributetype ( 2.16.840.1.101.2.2.1.118
    NAME 'mailDomains'
    DESC 'The domains that a messaging gateway will bridge'
    EQUALITY caseIgnoreMatch
    SUBSTR caseIgnoreSubstringsMatch
    SYNTAX 1.3.6.1.4.1.1466.115.121.1.15 )

attributetype (0.9.2342.19200300.100.1.10
    NAME 'manager'
    EQUALITY distinguishedNameMatch
    SYNTAX 1.3.6.1.4.1.1466.115.121.1.12 )

attributetype ( 2.16.840.1.101.2.2.1.162
    NAME 'maxMessageSize'
    DESC 'The maximum message size (in kilobytes) which may be received by the
mailbox'
    EQUALITY integerMatch
    SINGLE-VALUE
    SYNTAX 1.3.6.1.4.1.1466.115.121.1.27 )

attributetype (2.5.4.31
    NAME 'member'
    SUP distinguishedName )

attributeType (2.6.5.2.14
    NAME ('mhsDLRelatedLists' 'mhs-dl-related-lists')
    SUP distinguishedName
    SYNTAX '1.3.6.1.4.1.1466.115.121.1.12' )

attributeType (2.6.5.2.4
    NAME ('mhsDLSubmitPermissions' 'mhs-dl-submit-permissions')
    EQUALITY 'caseIgnoreMatch'
    SUBSTR 'caseIgnoreSubstringsMatch'
    SYNTAX 1.3.6.1.4.1.1466.115.121.1.15 )

attributeType (2.6.5.2.0
    NAME ('mhsMaximumContentLength' 'mhs-maximum-content-length')
    EQUALITY integerMatch
    SINGLE-VALUE
    SYNTAX '1.3.6.1.4.1.1466.115.121.1.27' )

attributeType (2.6.5.2.6
    NAME ('mhsORAddresses' 'mhs-or-addresses')
    EQUALITY 'caseIgnoreMatch'
    SUBSTR 'caseIgnoreSubstringsMatch'
    SYNTAX 1.3.6.1.4.1.1466.115.121.1.15 )

```

```

attributetype ( 2.16.840.1.101.2.2.1.119
  NAME 'militaryFacsimileNumber'
  DESC 'A military facsimile number, such as a DSN or DSTF number'
  SUP aCPTelephoneFaxNumber )

attributetype ( 2.16.840.1.101.2.2.1.160
  NAME 'militaryIPPhoneNumber'
  DESC 'A military telephone number that identifies an IP subscriber'
  SUP aCPTelephoneFaxNumber
  SYNTAX 1.3.6.1.4.1.1466.115.121.1.44 )

attributetype ( 2.16.840.1.101.2.2.1.120
  NAME 'militaryTelephoneNumber'
  SUP aCPTelephoneFaxNumber )

attributetype ( 2.16.840.1.101.2.2.1.64
  NAME 'minimize'
  DESC 'Whether the entry is under the MINIMIZE condition'
  EQUALITY booleanMatch
  SINGLE-VALUE
  SYNTAX 1.3.6.1.4.1.1466.115.121.1.7 )

attributetype ( 2.16.840.1.101.2.2.1.65
  NAME 'minimizeOverride'
  DESC 'Whether the Message Conversion System (MCS) can override the MINIMIZE
condition'
  EQUALITY booleanMatch
  SINGLE-VALUE
  SYNTAX 1.3.6.1.4.1.1466.115.121.1.7 )

attributetype (0.9.2342.19200300.100.1.41
  NAME ( 'mobile' 'mobileTelephoneNumber' )
  EQUALITY telephoneNumberMatch
  SUBSTR telephoneNumberSubstringsMatch
  SYNTAX 1.3.6.1.4.1.1466.115.121.1.50 )

attributetype ( 2.16.840.1.101.2.2.1.163
  NAME 'msgProtocolInfoCapability'
  DESC 'The messaging protocols supported by the mailbox'
  EQUALITY integerMatch
  SINGLE-VALUE
  SYNTAX 1.3.6.1.4.1.1466.115.121.1.27 )

attributeType (2.5.4.41
  NAME 'name'
  EQUALITY caseIgnoreMatch
  SUBSTR caseIgnoreSubstringsMatch
  SYNTAX '1.3.6.1.4.1.1466.115.121.1.15')

attributetype ( 2.16.840.1.101.2.2.1.56
  NAME 'nameClassification'
  DESC 'The security classification of the name of the entry itself'
  EQUALITY integerMatch
  SYNTAX 1.3.6.1.4.1.1466.115.121.1.27)

attributetype (2.16.840.1.101.2.2.1.68
  NAME 'nationality'
  DESC 'The name of the country which owns the entry'
  SUP name
  SINGLE-VALUE
  SYNTAX 1.3.6.1.4.1.1466.115.121.1.44)

attributetype (2.5.4.0
  NAME 'objectClass'
  EQUALITY objectIdentifierMatch
  SYNTAX 1.3.6.1.4.1.1466.115.121.1.38 )

attributetype ( 2.5.4.11
  NAME ( 'ou' 'organizationalUnitName' )
  SUP name )

```

```

attributetype ( 2.5.4.10
    NAME ( 'o' 'organizationName' )
    SUP name )

attributetype (2.5.4.32
    NAME 'owner'
    SUP distinguishedName )

attributetype (0.9.2342.19200300.100.1.42
    NAME ( 'pager' 'pagerTelephoneNumber' )
    EQUALITY telephoneNumberMatch
    SUBSTR telephoneNumberSubstringsMatch
    SYNTAX 1.3.6.1.4.1.1466.115.121.1.50 )

attributetype (0.9.2342.19200300.100.1.7
    NAME 'photo'
    SYNTAX 1.3.6.1.4.1.1466.115.121.1.23{25000} )

attributetype ( 2.5.4.19
    NAME 'physicalDeliveryOfficeName'
    EQUALITY caseIgnoreMatch
    SUBSTR caseIgnoreSubstringsMatch
    SYNTAX 1.3.6.1.4.1.1466.115.121.1.15{128} )

attributetype ( 2.16.840.1.101.2.2.1.71
    NAME 'plaAddressees'
    DESC 'The list of action and information addressees of the collective'
    EQUALITY caseIgnoreMatch
    SUBSTR caseIgnoreSubstringsMatch
    SYNTAX 1.3.6.1.4.1.1466.115.121.1.44)

attributetype ( 2.16.840.1.101.2.2.1.70
    NAME 'planameACP127'
    DESC 'The ACP127/JANAP128 plain language address'
    SUP name
    SINGLE-VALUE
    SYNTAX 1.3.6.1.4.1.1466.115.121.1.44)

attributetype ( 2.16.840.1.101.2.2.1.72
    NAME 'plaReplace'
    DESC 'Whether the Message Conversion System (MCS), should replace alternate
spellings with the "primary", or correct, spelling'
    EQUALITY booleanMatch
    SINGLE-VALUE
    SYNTAX 1.3.6.1.4.1.1466.115.121.1.7 )

attributetype ( 2.16.840.1.101.2.2.1.125
    NAME 'positionNumber'
    DESC 'An individual's position and possibly roles and duties, with the
organization'
    EQUALITY caseIgnoreMatch
    SUBSTR caseIgnoreSubstringsMatch
    SYNTAX 1.3.6.1.4.1.1466.115.121.1.15 )

attributetype ( 2.5.4.16
    NAME 'postalAddress'
    EQUALITY caseIgnoreListMatch
    SUBSTR caseIgnoreListSubstringsMatch
    SYNTAX 1.3.6.1.4.1.1466.115.121.1.41 )

attributetype ( 2.5.4.17
    NAME 'postalCode'
    EQUALITY caseIgnoreMatch
    SUBSTR caseIgnoreSubstringsMatch
    SYNTAX 1.3.6.1.4.1.1466.115.121.1.15{40} )

attributetype ( 2.5.4.18
    NAME 'postOfficeBox'
    EQUALITY caseIgnoreMatch
    SUBSTR caseIgnoreSubstringsMatch
    SYNTAX 1.3.6.1.4.1.1466.115.121.1.15{40} )

attributetype (2.5.4.28

```

```

NAME 'preferredDeliveryMethod'
SYNTAX 1.3.6.1.4.1.1466.115.121.1.14
SINGLE-VALUE )

attributetype (2.16.840.1.113730.3.1.39
NAME 'preferredLanguage'
DESC 'RFC2798: preferred written or spoken language for a person'
EQUALITY caseIgnoreMatch
SUBSTR caseIgnoreSubstringsMatch
SYNTAX 1.3.6.1.4.1.1466.115.121.1.15
SINGLE-VALUE )

attributetype ( 2.16.840.1.101.2.2.1.73
NAME 'primarySpellingACPI127'
DESC 'The correct PLA spelling'
EQUALITY caseIgnoreMatch
SUBSTR caseIgnoreSubstringsMatch
SINGLE-VALUE
SYNTAX 1.3.6.1.4.1.1466.115.121.1.44 )

attributetype ( 2.16.840.1.101.2.2.1.126
NAME 'proprietaryMailboxes'
DESC 'Mailboxes within the local proprietary domain, such as CC:Mail'
EQUALITY caseIgnoreMatch
SUBSTR caseIgnoreSubstringsMatch
SYNTAX 1.3.6.1.4.1.1466.115.121.1.15 )

attributetype ( 2.16.840.1.101.2.2.1.74
NAME 'publish'
DESC 'Whether the PLA should be published in the Message Address Directory or
the ACPI117'
EQUALITY booleanMatch
SINGLE-VALUE
SYNTAX 1.3.6.1.4.1.1466.115.121.1.7 )

attributetype ( 2.16.840.1.101.2.2.1.133
NAME 'rank'
DESC 'The military or civilian rank of an individual'
EQUALITY caseIgnoreMatch
SUBSTR caseIgnoreSubstringsMatch
SYNTAX 1.3.6.1.4.1.1466.115.121.1.15 )

attributetype ( 2.16.840.1.101.2.2.1.75
NAME 'recapDueDate'
DESC 'The date and time when the list is expected to be recapped or validated'
EQUALITY generalizedTimeMatch
SINGLE-VALUE
SYNTAX 1.3.6.1.4.1.1466.115.121.1.24 )

attributetype (2.5.4.26
NAME 'registeredAddress'
SUP postalAddress
SYNTAX 1.3.6.1.4.1.1466.115.121.1.41 )

attributetype ( 2.16.840.1.101.2.2.1.76
NAME 'remarks'
EQUALITY caseIgnoreMatch
SUBSTR caseIgnoreSubstringsMatch
SYNTAX 1.3.6.1.4.1.1466.115.121.1.15 )

attributetype ( 2.16.840.1.101.2.2.1.77
NAME 'rI'
DESC 'The rI (Routing Indicator) for a user's PLA name'
EQUALITY caseIgnoreMatch
SUBSTR caseIgnoreSubstringsMatch
SYNTAX 1.3.6.1.4.1.1466.115.121.1.44 )

attributetype ( 2.16.840.1.101.2.2.1.78
NAME 'rIClassification'
DESC 'The highest security classification of data allowed to process by the
entry'
EQUALITY integerMatch
SYNTAX 1.3.6.1.4.1.1466.115.121.1.27)

```



```

attributetype ( 2.16.840.1.101.2.2.1.79
  NAME 'rInfo'
  DESC 'Routing indicators with associated properties'
  EQUALITY caseIgnoreMatch
  SUBSTR caseIgnoreSubstringsMatch
  SYNTAX 1.3.6.1.4.1.1466.115.121.1.15 )

attributetype (2.5.4.33
  NAME 'roleOccupant'
  SUP distinguishedName )

attributetype (0.9.2342.19200300.100.1.6
  NAME 'roomNumber'
  EQUALITY caseIgnoreMatch
  SUBSTR caseIgnoreSubstringsMatch
  SYNTAX 1.3.6.1.4.1.1466.115.121.1.15{256} )

attributetype ( 2.5.4.14
  NAME 'searchGuide'
  SYNTAX 1.3.6.1.4.1.1466.115.121.1.15 )

attributetype ( 2.16.840.1.101.2.2.1.80
  NAME 'secondPartyAddressees'
  DESC 'The second party addressees who are expected to take appropriate action
on message'
  EQUALITY caseIgnoreMatch
  SUBSTR caseIgnoreSubstringsMatch
  SYNTAX 1.3.6.1.4.1.1466.115.121.44 )

attributetype (0.9.2342.19200300.100.1.21
  NAME 'secretary'
  EQUALITY distinguishedNameMatch
  SYNTAX 1.3.6.1.4.1.1466.115.121.1.12 )

attributetype ( 2.16.840.1.101.2.2.1.81
  NAME 'section'
  DESC 'Whether the receiving PLA requires message sectioning to be performed'
  EQUALITY booleanMatch
  SINGLE-VALUE
  SYNTAX 1.3.6.1.4.1.1466.115.121.1.7 )

attributetype ( 2.16.840.1.101.2.2.1.127
  NAME 'secureFacsimileNumber'
  DESC 'The facsimile number that is used for secure communications'
  SUP aCPTelephoneFaxNumber )

attributetype ( 2.16.840.1.101.2.2.1.128
  NAME 'secureTelephoneNumber'
  DESC 'The telephone number of a secure device, such as STU II or STU III'
  SUP aCPTelephoneFaxNumber )

attributetype (2.5.4.34
  NAME 'seeAlso'
  SUP distinguishedName )

attributetype (2.5.4.5
  NAME 'serialNumber'
  EQUALITY caseIgnoreMatch
  SUBSTR caseIgnoreSubstringsMatch
  SYNTAX 1.3.6.1.4.1.1466.115.121.1.44{64} )

attributetype ( 2.16.840.1.101.2.2.1.129
  NAME 'serviceNumber'
  DESC 'The staff identifier number, such as payroll references, medical records,
human resources and duty rosters'
  EQUALITY caseIgnoreMatch
  SUBSTR caseIgnoreSubstringsMatch
  SYNTAX 1.3.6.1.4.1.1466.115.121.1.15 )

attributetype ( 2.16.840.1.101.2.2.1.82
  NAME 'serviceOrAgency'
  DESC 'The service or agency to which the PLA belongs'

```

```

EQUALITY caseIgnoreMatch
SUBSTR caseIgnoreSubstringsMatch
SINGLE-VALUE
SYNTAX 1.3.6.1.4.1.1466.115.121.1.44 )

attributetype ( 2.16.840.1.101.2.2.1.83
  NAME 'sHD'
  DESC 'The sHD (special Handling Designator) which an entity, address or routing
indicator can support'
  EQUALITY caseIgnoreMatch
  SUBSTR caseIgnoreSubstringsMatch
  SYNTAX 1.3.6.1.4.1.1466.115.121.1.44 )

attributetype ( 2.16.840.1.101.2.2.1.84
  NAME 'shortTitle'
  DESC 'The PLA name used for Signal Intelligence (SIGINT) related
communications'
  EQUALITY caseIgnoreMatch
  SUBSTR caseIgnoreSubstringsMatch
  SINGLE-VALUE
  SYNTAX 1.3.6.1.4.1.1466.115.121.1.44 )

attributetype ( 2.16.840.1.101.2.2.1.85
  NAME 'sigad'
  DESC 'The PLA name used for sensitive SIGINT related communications'
  EQUALITY caseIgnoreMatch
  SUBSTR caseIgnoreSubstringsMatch
  SINGLE-VALUE
  SYNTAX 1.3.6.1.4.1.1466.115.121.1.44 )

attributetype ( 2.16.840.1.101.2.2.1.86
  NAME 'spot'
  DESC 'The special project address list or collective'
  EQUALITY caseIgnoreMatch
  SUBSTR caseIgnoreSubstringsMatch
  SINGLE-VALUE
  SYNTAX 1.3.6.1.4.1.1466.115.121.1.44 )

attributetype ( 2.5.4.8
  NAME ( 'st' 'stateOrProvinceName' )
  SUP name )

attributetype ( 2.5.4.9
  NAME ( 'street' 'streetAddress' )
  EQUALITY caseIgnoreMatch
  SUBSTR caseIgnoreSubstringsMatch
  SYNTAX 1.3.6.1.4.1.1466.115.121.1.15{128} )

attributetype ( 2.5.4.52
  NAME 'supportedAlgorithms'
  SYNTAX 1.3.6.1.4.1.1466.115.121.1.49)

attributetype (2.5.4.4
  NAME ( 'sn' 'surname' )
  SUP name )

attributetype ( 2.16.840.1.101.2.2.1.87
  NAME 'tARE'
  DESC 'The delivery responsibility for a message that is received by an
intermediary'
  EQUALITY booleanMatch
  SINGLE-VALUE
  SYNTAX 1.3.6.1.4.1.1466.115.121.1.7 )

attributetype ( 2.16.840.1.101.2.2.1.96
  NAME 'tCC'
  DESC 'The handling instruction used in the routing indicator'
  EQUALITY caseIgnoreMatch
  SUBSTR caseIgnoreSubstringsMatch
  SINGLE-VALUE
  SYNTAX 1.3.6.1.4.1.1466.115.121.1.44 )

```

```

attributetype ( 2.16.840.1.101.2.2.1.144
    NAME 'tCCG'
    DESC 'A group of message handling instructions used in the routing indicator'
    EQUALITY caseIgnoreMatch
    SUBSTR caseIgnoreSubstringsMatch
    SYNTAX 1.3.6.1.4.1.1466.115.121.1.44 )

attributetype ( 2.5.4.20
    NAME 'telephoneNumber'
    EQUALITY telephoneNumberMatch
    SUBSTR telephoneNumberSubstringsMatch
    SYNTAX 1.3.6.1.4.1.1466.115.121.1.50{32} )

attributetype (2.5.4.22
    NAME 'teletexTerminalIdentifier'
    SYNTAX 1.3.6.1.4.1.1466.115.121.1.51 )

attributetype (2.5.4.21
    NAME 'telexNumber'
    SYNTAX 1.3.6.1.4.1.1466.115.121.1.52 )

attributetype ( 2.5.4.12
    NAME 'title'
    SUP name )

attributetype ( 2.16.840.1.101.2.2.1.69
    NAME 'transferStation'
    DESC 'Whether a message for the entry should be sent to a communications
processing and routing system, called a transfer station. For example, NAVCOMPARS'
    EQUALITY booleanMatch
    SINGLE-VALUE
    SYNTAX 1.3.6.1.4.1.1466.115.121.1.7 )

attributetype ( 2.16.840.1.101.2.2.1.97
    NAME 'trc'
    DESC 'The classification of data used in the routing indicator'
    EQUALITY caseIgnoreMatch
    SUBSTR caseIgnoreSubstringsMatch
    SINGLE-VALUE
    SYNTAX 1.3.6.1.4.1.1466.115.121.1.44 )

attributetype (0.9.2342.19200300.100.1.1
    NAME ( 'uid' 'userid' )
    DESC 'RFC1274: user identifier'
    EQUALITY caseIgnoreMatch
    SUBSTR caseIgnoreSubstringsMatch
    SYNTAX 1.3.6.1.4.1.1466.115.121.1.15{256} )

attributetype ( 2.16.840.1.101.2.2.1.145
    NAME 'usdConversion'
    DESC 'The organizational address that is used when other types of address are
not appropriate'
    EQUALITY caseIgnoreMatch
    SUBSTR caseIgnoreSubstringsMatch
    SYNTAX 1.3.6.1.4.1.1466.115.121.1.15 )

attributetype (2.5.4.36
    NAME 'userCertificate'
    EQUALITY CertificateExactMatch
    SYNTAX 1.3.6.1.4.1.1466.115.121.1.8 )

attributetype (2.5.4.35
    NAME 'userPassword'
    EQUALITY octetStringMatch
    SYNTAX 1.3.6.1.4.1.1466.115.121.1.40{128} )

attributetype (2.16.840.1.113730.3.1.216
    NAME 'userPKCS12'
    DESC 'RFC2798: PKCS #12 PFX PDU for exchange of personal identity information'
    EQUALITY octetStringMatch
    SYNTAX 1.3.6.1.4.1.1466.115.121.1.40 )

attributetype (2.16.840.1.113730.3.1.40

```

```
NAME 'userSMIMECertificate'
DESC 'RFC2798: PKCS#7 SignedData used to support S/MIME'
EQUALITY octetStringMatch
SYNTAX 1.3.6.1.4.1.1466.115.121.1.40 )

attributetype ( 2.16.840.1.101.2.1.5.167
  NAME 'webAccessCapability'
  DESC 'Whether the entry is capable of accessing a web-based Bulletin Board
service to download or access information'
  EQUALITY booleanMatch
  SINGLE-VALUE
  SYNTAX 1.3.6.1.4.1.1466.115.121.1.7)

attributetype (2.5.4.24
  NAME 'x121Address'
  EQUALITY numericStringMatch
  SUBSTR numericStringSubstringsMatch
  SYNTAX 1.3.6.1.4.1.1466.115.121.1.36{15} )

attributetype (2.5.4.45
  NAME 'x500UniqueIdentifier'
  EQUALITY bitStringMatch
  SYNTAX 1.3.6.1.4.1.1466.115.121.1.6 )
```